

# Material Safety Data Sheet

## #019

### Flammable Outdoor Carpet Adhesive

#### SECTION I - PRODUCT IDENTIFICATION

Manufacturer's Name: Capitol Adhesives  
Address: 300 Cross Plains Blvd., Dalton, GA 30720  
Telephone #: 1-800-831-8381  
Generic ID: Flammable SBR Rubber Adhesive in solvent solution  
DOT Hazard Classification: None  
Product Identity: #019 Exterior Carpet Adhesive

#### SECTION II - HAZARDOUS COMPONENTS

	% (weight)	PEL	TLV
Mineral Spirits (CAS# 8052-41-3)	17.2	100ppm	100ppm
Toluene (CAS # 108-88-3)	12.3%	100ppm	100ppm

#### SECTION III - PHYSICAL DATA

Initial Boiling Point: 200°F  
Vapor Pressure: 83.0 mm Hg @ 100°F  
Vapor Density (Air=1.0): 3.60  
Specific Gravity: 1.2  
Percent Volatiles: 29.5%

#### SECTION IV - FIRE AND EXPLOSION DATA

Flash Point: 32°F  
Explosive Limit (Product): Lower=1, Upper=6  
Extinguishing Media: Foam, CO<sub>2</sub>, Dry Chemical

**HAZARDOUS DECOMPOSITION PRODUCTS:** May form toxic materials: carbon dioxide and carbon monoxide, various hydrocarbons, etc.

**SPECIAL FIRE FIGHTING PROCEDURES:** Water may be used to keep fire-exposed containers cool until fire is out. Wear self contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode when fighting fires.

**UNUSUAL FIRE & EXPLOSION HAZARDS:** Never use welding or cutting torch on or near cans (even empty) because resultant pressure could rupture. Empty cans should be incinerated.

#### SECTION V - HEALTH HAZARD DATA

Permissible Exposure Level: 100 ppm  
Threshold Limit Value: 100 ppm

**EFFECTS OF EXPOSURE:** Eyes- Can cause irritation, redness, tearing, blurred vision. Skin- Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis. Breathing- Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, and even asphyxiation. Swallowing- Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

**First Aid:** Skin- Soap and water. Eyes- Flush with water, lifting upper and lower lids occasionally. Ingestion- Do not induce vomit-

ing. Call physician or transport to an emergency facility. Inhalation- If affected, remove individual to fresh air. Use only in well ventilated areas.

#### SECTION VI - REACTIVITY DATA

Stability: Stable  
Incompatibility: None  
Hazardous Decomposition: None  
Hazardous Polymerization: Cannot Occur  
Conditions To Avoid: None Known

#### SECTION VII - SPILL OR LEAK PROCEDURES

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Absorb liquid on paper, vermiculite, floor absorbent, or other absorbent material and transfer to hood. Allow volatile portion to evaporate in hood. Allow sufficient time for vapors to completely clear hood duct work. Dispose of remaining material in accordance with applicable regulations.

#### SECTION VIII - PROTECTIVE EQUIPMENT

**VENTILATION:** Adequate ventilation is essential to prevent vapor build-up. Open all available windows and entrances to insure good ventilation. **RESPIRATOR PROTECTION:** Adequate ventilation is normally sufficient. If eyes begin to water or dizziness or headaches are experienced, increase fresh air supply, wear an NIOSH approved respirator, or leave the area. **PROTECTIVE GLOVES:** Wear protective gloves to prevent skin contact. **EYE PROTECTION:** Wear glasses or protective goggles to avoid splashes. **OTHER PROTECTIVE EQUIPMENT:** None required. **WASH HANDS THOROUGHLY WITH SOAP AND WATER.**

#### SECTION IX - SPECIAL PRECAUTIONS

Protect from freezing. Use only in applications as stated on the label. Do not take internally. Close container after each use. Avoid skin and eye contact.

Ventilation with fresh air, including open doors and windows should be observed during any flooring installation. Operate HVAC systems at 100% fresh air intake before, during and after installation to eliminate lingering odors or particulate matter.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with company or not. Recipients are advised to confirm in advance of need that the information is current, applicable and suitable to their circumstances.

**KEEP OUT OF REACH OF CHILDREN**



Capitol Adhesives, Inc.  
PO Box 2023  
300 Cross Plains Blvd.  
Dalton, Georgia 30720